

INSTALLATION, SERVICE AND MAINTENANCE INSTRUCTIONS

ANNEX FOR CE ATEX REGISTERED EQUIPMENT UNDER DIRECTIVE 2014/34/EU:

CHECK VALVES Ex

The contents of this Annex complement the information included in the instruction manual. The instructions in this Annex must be observed whenever equipment registered under Directive 2014/34/EU is used.

If applicable, this Annex shall be complemented by the manuals of ATEX-certified components which form part of the unit (e.g., seals).



Original Manual

10.501.30.03EN (A) 2022/11



EU Declaration of Conformity ATEX 2014/34/EU

We,

INOXPA, S.A.U.

Telers, 60 17820 – Banyoles (Girona)

Hereby declare under our sole responsibility that the machine

VALVE

Model


CHECK

From serial number **IXXXXXXXXX** to **IXXXXXXXXX** (1)

Fulfills all the relevant provisions of Safety and Health from ATEX 2014/34/EU Directive and are adapted to the harmonized norms:

EN ISO 80079-36:2016 EN ISO 80079-37:2016 EN 1127-1:2019 EN 13237:2012 EN 15198:2007

This Declaration of Conformity covers equipment with the following ATEX marking:



The technical documentation referenced 018400/15 is on file with the notified body INSTITUT NATIONAL DE L'ENVIRONNEMENT INDUSTRIEL ET DES RISQUES (INERIS), Parc Technologique Alata BP 2, 60550 Verneuil-en-Halatte, France. Reference num. 0080.

Signed by and on behalf of:

INOXPA, S.A.U.

David Reyero Brunet Technical Office Manager Banyoles, 2022



1. Safety

- 1.1. INSTRUCTIONS MANUAL
- 1.2. INSTRUCTIONS FOR STARTING UP
- **1.3. SAFETY**
- 1.3.1. Warning symbols



Danger! Important indications regarding protection from explosions

1.4. GENERAL SAFETY INSTRUCTIONS

1.4.1. During installation

In order to reduce the risk of static electricity, the equipment must be earthed to ensure electrical continuity between the pipes and the valve

1.4.2. During operation

The limits of the operating conditions in explosive atmospheres must not be exceeded

This valve was selected according to the operating conditions specified by the user. Therefore, INOXPA disclaims liability for any damage caused by use of the valve in conditions other than those stated in the order

1.4.3. During maintenance



Danger! Important indications regarding protection from explosions.

An explosive atmosphere may be created during disassembly of the valve. Therefore, safe work permits must be issued and these jobs must only be done by qualified or trained personnel

1.4.4. Compliance with the instructions

Any non-fulfilment of the instructions may result in a risk for the operators, the environment and the machine, and may result in the loss of your right to claim damages.

Non-fulfilment may cause the following risks (in addition to those indicated in the manual):

- Creation of explosive atmospheres and risk of explosion.



1.5. GUARANTEE

Any guarantee will be lawfully cancelled immediately; in addition, we will be compensated for any claims of civil liability presented by third parties, in the case that (further to the conditions already indicated in the manual):

- The equipment has been used improperly or has not been used in accordance with the working conditions in the classified area, work has been carried out in a different classified area, or different conditions of temperature or pressure and/or different substances have been used.



2. Table of Contents

The indications of such sections must be observed in addition to those of the valve manual.

1. Safety	
1.1. Instructions manual	3
1.2. Instructions for starting up	3
1.3. Safety	3
1.4. General safety instructions	3
1.5. Guarantee	4
2. Table of Contents	
3. Receipt and installation	
3.1. Checking the shipment	6
3.2. Delivery and unpacking	6
3.3. Identification	6
3.4. Positioning	7
3.5. Assembly	7
3.6. Inspecting and checking	7
3.7. Welding	7
4. Start-up	
4.1. Start up	9
4.2. Operation	9
5. Operating problems Causes and solutions	
6. Maintenance	
6.1. General points	11
6.2. Maintenance	11
6.3. Cleaning	12
7. Assembly and disassembly	
7.1. Disassembling/assembling the valve	13
7.2. Positioning the check valve	13
7.3. Technical specifications	14
7.4. Weld/weld check valve dimensions	15
7.5. Section and parts list	16
7.6. Parts list	16



3. Receipt and installation

3.1. CHECKING THE SHIPMENT


The received valve must be checked to ensure that it is adapted to the working conditions of the classified area and the conditions of the order

3.2. DELIVERY AND UNPACKING

- **3.2.1. Delivery**
- 3.2.2. Unpacking

3.3. IDENTIFICATION

The following additional information shall identify ATEX valves:



The temperature class and the maximum surface temperature depend on the temperature of the product to be stirred and the ambient temperature.

Temperature class for explosive gas atmospheres

	1 2	
Temperature	Product temperature (in process	Room temperature
class	or cleaning)	Room temperature
T6	≤ 60 °C	
T5	≤ 75 °C	-20 °C to +40 °C
T4	≤110 °C	-20 C to +40 C
T3	≤ 140 °C	

Maximum surface temperature for explosive dust atmospheres

waximum surface temperature for explosive dust atmospheres			
Maximum surface temperature	Product temperature (in process or cleaning)	Room temperature	
T85 °C	≤ 85 °C		
T100 °C	≤ 100 °C	20 °C to 140 °C	
T125 ℃	≤ 125 °C	-20 °C to +40 °C	
T 200 °C	< 200 °C		

3.4. POSITIONING

3.5. ASSEMBLY

In order to reduce the risk of static electricity, the equipment must be earthed to ensure electrical continuity between the pipes and the valve

3.6. INSPECTING AND CHECKING



3.7. WELDING

Safe-work permits will be required for any welding work in potentially explosive atmospheres. It is strongly recommended that this type of work be carried out in non-classified atmospheres (i.e. there must not be an explosive atmosphere in the location of the valve when it is being handled)

3.7.1. WELD/WELD CHECK VALVE



4. Start-up

4.1. STARTING UP

The received valve must be checked to ensure that it is adapted to the working conditions of the classified area and the conditions of the order

Ensure that there is an uninterrupted supply of electricity between the valve and that installation, and that the installation is earthed

4.2. OPERATION

Do not modify the operating parameters for which the valve has been designed without written prior authorisation from INOXPA

The valve was selected for specific working conditions in potentially explosive atmospheres at the time the order was placed. INOXPA will not be responsible for any damage caused if the information provided by the buyer is incomplete or incorrect (type of liquid, viscosity, classification of the potentially explosive zone, gas generated by the potentially explosive atmosphere, etc.)



6. Maintenance

6.1. GENERAL INFORMATION

The valves shall only be assembled and disassembled by qualified staff and safe work permits must be obtained for potentially atmospheric atmospheres.

- **6.2. MAINTENANCE**
- 6.2.1. Maintenance of the seals.
- **6.2.2.** Storage
- **6.2.3. Spare parts**

When ordering spare parts for a valve to work in a classified zone, it is necessary to explicitly indicate on the order that they are for a valve operating in an ATEX zone, and to indicate the characteristics of this zone.

Otherwise, INOXPA cannot ensure that the valve will operate with parts that are suitable for the classified area within which it is installed.

6.3. CLEANING

Before starting disassembly and assembly work, it is necessary to take into account the presence or possible formation of potentially explosive atmospheres



7. Assembly and disassembly

The valves shall only be assembled and disassembled by qualified staff and safe work permits must be obtained for potentially atmospheric atmospheres

- 7.1. DISASSEMBLY / ASSEMBLY OF THE CHECK VALVE
- 7.2. POSITIONING OF THE CHECK VALVE
- 7.3. TECHNICAL SPECIFICATIONS

Temperature range. See section 3.3.

- 7.4. WELD/WELD CHECK VALVE DIMENSIONS
- 7.5. SECTION AND PARTS LIST
- 7.6. PARTS LIST